



HIND MOULD RELEASE WT

PRODUCT DATA SHEET

EMULSIFIED MINERAL OIL BASED WATER THINABLE MOULD RELEASING AGENT.

DESCRIPTION

Hind Mould Release WT is a combination of refined emulsified mineral oil. When diluted with water, it produces a chemical release agent. It has the economy of conventional oil with outstanding properties of a stable release agent.

USES

- To Provide quick, clean and easy stripping of Concrete moulds, Mivan shuttering and Aluminum form work.
- To obtain clean and smooth concrete surface.
- To protect steel and wooden form work.

ADVANTAGES

- Requires only water for use. Minimum cleaning of shutters before re-use.
- Extended life of form work.
- Can be used on all types of form work.
- Improved finish: stain and air free fair faced concrete.
- Non corrosive to steel.
- Dirt-free concrete surface.

APPLICATION

Apply one coat only by brush, roller or spray on the clean surface. **Hind Mould Release WT** after application should be allowed to dry before concreting takes place.

PROPERTIES

Aspect	Light brown liquid
Coverage(After dilution)	30 to 40 Sq. mtr /Litre (Wood)
Dilution Rate- Hind Mould Release WT : Water = 1:6	40 to 50Sq. mtr /Litre (Steel or plastic)

SHELF LIFE

Best before 12 months from the date of manufacture in unopened condition. Should be stored in a cool and dry place away from direct sunlight and naked flame at temperature ranging between 2⁰ C (Min.) and 40⁰ C (Max.)

PACKING

100, 200 Litre, HDPE container or as required.

HANDLING PRECAUTIONS

Hind Mould Release WT is non-toxic and ingestion to be avoided. Any splashes to the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice.

Note:

- **Hindcon Chemicals** maintains a team of technically trained professionals to provide full support to your problems in construction, and recommend the correct product to suite your specific requirements. Our authorized applicators can attend your site for application of the products.
- The content of the Technical datasheet are for general information and guideline. The result shown here are generated from our laboratory or from our site experiences.
- Quality of our products are maintained as per ISO9001:2008 recommendations and continuous researches. The behavior can change as per the prevailing conditions at the time of applications.
- Since **HINDCON CHEMICALS LIMITED** has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular circumstances, the result that the user will obtain from the product will be the same as those described in this communication or that the user will find the information or recommendations complete, accurate or useful. The client must test and ascertain the safety and fitness for the product for use.
- The right to change the properties of the products is reserved with us. The proprietary rights of third parties must be observed. All orders are accepted subject to the terms of sale and delivery. Users must always refer to the most recent issue of the latest Data Sheet for the product concerned, copies of which will be supplied on request.

HINDCON CHEMICALS LIMITED

(AN ISO 9001: 2015 COMPANY)

Office:

62B, Braunfeld Row, "VASUDHA", Kolkata - 700027

Tel: 24490839. Fax: 24490849

E-mail: contactus@hindcon.com, hindconchemicals@yahoo.com

Factory:

Baniyara, Jalan Complex, Gate No.3

Howrah – 711 411

www.hindcon.com