



HIND PLUG - S

PRODUCT DATA SHEET

A QUICK SETTING READY TO USE POWDERED COMPOUND

DESCRIPTION

Hind Plug S is fast setting powdered compound for stopping running water.

USES

It is used to stop running water and seepage through concrete and masonry walls, dams etc.

ADVANTAGES

- Stops running water immediately
- Non shrink and Non-metallic.
- High strength.
- Easy to use.
- Sets under water.

APPLICATION

Chisel the masonry around the crack to a width & depth not less than 25 mm. The hole should be wider within the wall than at the surface. Mix **Hind Plug S** in the ratio of 0.28 to 0.33 (Water/powder ratio). Force the material into the crack when heat generation is felt. Hold tightly with hand for 3 minutes, wearing rubber hand gloves.

PROPERTIES

Aspect	Light Brown Powder
Setting at 27 ⁰ C	1 to 3 minutes
Compressive Strength	8 N/mm ² (minimum) after 1 hour 19 N/mm ² (minimum) after 24 hour

SHELF LIFE

Best before 6 months from the date of manufacture. Should be stored in a cool and dry place away from direct sunlight at temperature ranging between 2⁰ C (Min.) and 45⁰ C (Max.).

PACKING

Available in 25 Kg. HDPE Bag

HANDLING PRECAUTION

Hind Plug S is non-toxic and ingestion is to be avoided. If contact with eyes occurs, wash well immediately with water and seek medical advice.

Note:

- **Hindcon Chemicals** maintains a team of technically trained professionals to provide full support to your problems in construction, and recommend the correct product to suite your specific requirements. Our authorized applicators can attend your site for application of the products.
- The content of the Technical datasheet are for general information and guideline. The result shown here are generated from our laboratory or from our site experiences.
- Quality of our products are maintained as per ISO9001:2008 recommendations and continuous researches. The behavior can change as per the prevailing conditions at the time of applications.
- Since **HINDCON CHEMICALS LIMITED** has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular circumstances, the result that the user will obtain from the product will be the same as those described in this communication or that the user will find the information or recommendations complete, accurate or useful. The client must test and ascertain the safety and fitness for the product for use.
- The right to change the properties of the products is reserved with us. The proprietary rights of third parties must be observed. All orders are accepted subject to the terms of sale and delivery. Users must always refer to the most recent issue of the latest Data Sheet for the product concerned, copies of which will be supplied on request.

HINDCON CHEMICALS LIMITED

(AN ISO 9001: 2015 COMPANY)

Office:
62B, Braunfeld Row, "VASUDHA", Kolkata - 700027
Tel: 24490839. Fax: 24490849
E-mail: contactus@hindcon.com, hindconchemicals@yahoo.com

Factory:
Baniyara, Jalan Complex, Gate No.3
Howrah – 711 411
www.hindcon.com