

HIND MOULD RELEASE OB

MINERAL OIL BASED SHUTTER RELEASE AGENT



DESCRIPTION

Hind Mould Release OB Low viscous mineral oil based shutter release agent. Ready for direct application and use.

USES

HIND Mould Release OB can be used:

- To Provide quick, clean and easy stripping of Concrete moulds, Mivan shuttering and Aluminum form work.
- To obtain clean and smooth concrete surface.
- To protect steel and wooden form work.

ADVANTAGES

- Minimum cleaning of shutters before re-use.
- Extended life of form work.
- Can be used on all types of form work.
- Improved finish, stain and air free fair faced concrete.
- High coverage.
- Non corrosive to steel.
- Dust free concrete surface.

APPLICATION

Apply one coat only by brush, roller or spray on the clean surface. **Hind Mould Release OB** after application should be allowed to dry before concreting takes place.

PROPERTIES

Aspect	Light brownish/ Light greenish liquid
Coverage	20 to 50 Sq. mtr. /Litre The consumption depends on the surface texture and porosity of the form work.

SHELF LIFE

Best before 12 months from the date of manufacture in unopened condition. Should be stored in a cool and dry place away from direct sunlight at temperature ranging between 2°C (Min.) and 40°C (Max.)

HIND MOULD RELEASE OB

MINERAL OIL BASED SHUTTER RELEASE AGENT

PACKING

105, 210 Ltr. Container

HANDLING PRECAUTION

Hind Mould Release OB is non-toxic but ingestion is to be avoided. Any splashes to the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice.



IMPORTANT NOTICE :

Hindcon Chemicals maintains a team of technically trained professionals to provide full support to your problems in construction, and recommend the correct product to suite your specific requirements. Our authorized applicators can attend your site for application of the products. The content of the Technical datasheet are for general information and guideline. The result shown here are generated from our laboratory or from our site experiences.

Quality of our products are maintained as per ISO9001:2008 recommendations and continuous researches. The behaviour can change as per the prevailing conditions at the time of applications. Since **HINDCON CHEMICALS LIMITED** has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular circumstances, the result that the user will obtain from the product will be the same as those described in this communication or that the user will find the information or recommendations complete, accurate or useful. The client must test and ascertain the safety and fitness for the product for use. The right to change the properties of the products is reserved with us. The proprietary rights of third parties must be observed. All orders are accepted subject to the terms of sale and delivery. Users must always refer to the most recent issue of the latest Data Sheet for the product concerned, copies of which will be supplied on request.



✉ contactus@hindcon.com
☎ +91 33 24490839, 9830599113
☎ +91 33 24490849
📍 Kolkata, West Bengal, India

VISIT OUR WEBSITE

